

HECAT® MARK II PULSATOR®

The Original “Pulsating” Oil Cooler Flusher Trans, Engine, P/S, & Many Other Oil Coolers

**ECONOMICAL, DURABLE,
AND COMPACT MODEL**

The proven technology, powerful kinetic energy, and high flow rate of the PULSATOR® process (US Pat. #5615695); will remove the oils and debris from the parallel paths of even the most complex components. Something the spray can, little 1qt flush gun, and the laminar flow of simple circulating systems; just cannot.

Lifetime Warranty
with exclusive use of
SAFE-FLUSH® Trans.



INCLUDES:
Trans Cooler & Line
Adapter Kit & 2 Gal. of
SAFE-FLUSH® Trans.



NO LONGER USING RED DYE

- Incoming Air Filter. Cleanable Return T-Strainer. Activated Carbon Exhaust Vent Filter.
- High Quality Powder Coated Assembly. Laser Cut Stainless Control Panel.
- Return Line “Pop” Valve for a Quick Solvent Air Drying Validation Process.
- Air Operated “Pulse” Scrubbing Action. Frequency: 5 to 6 “pulses” Per Second.
- Scrubs into the Corners and Crevices to Loosen & Remove Stubborn Debris.
- Perfect for Small Shops, Mobile Services, Exporting, and Much More.
- Designed for Ease of Use, Storage, and Carry. 2-Gallon Solvent Capacity.
- Box Dim: 22”H x 22”W x 19”D. UPS weight: 65 lbs. Made in the USA.